



## DECLARATION OF PERFORMANCE

In accordance with the European Construction Products Regulation (UE) nº 305/2011

Nº C207

**1. Unique identifying code of the product:**

TILE ADHESIVE WHITE QUALITY PORCELANICO

**2. Intended Uses:**

Cementitious adhesive for applying ceramic tiles.

Use: indoors and outdoors

**3. Manufacturer:**

CEMI-COLA PORT, S.L. - C/ Isaac Newton, 83 –  
Pol. Industrial Sepes – 46500 SAGUNTO – VALENCIA – ESPAÑA – Tel. 96 2662762  
cemicola@cemicola.com – www. cemicola.com

**4. System or systems of assessment and verification of constancy of performance of the construction product (EVCP):**

Type 3 assessment system

**5. Harmonized standard:**

UNE-EN 12004-1:2017 Adhesives for ceramic tiles  
Notified body: LGAI Technological Center S.A. No 0370


**6. Declared performances:**

Characteristics	Performance	Test Method
Reaction to fire:	Class E	EN 13501-1
Adhesion: Initial Adhesion strength	≥ 0,5N/mm <sup>2</sup>	UNE- EN 12004-2:2017
Durability - Adhesion strength after immersion in water: - Adhesion strength after heat ageing: - Adhesion strength after freeze-thaw cycle:	≥ 0,5N/mm <sup>2</sup> ≥ 0,5N/mm <sup>2</sup> ≥ 0,5N/mm <sup>2</sup>	UNE- EN 12004-2:2017
Slippage	≤ 0,5 mm	UNE- EN 12004-2: 2017
Open time	≥ 0,5N/mm <sup>2</sup> Adhesion 30 min.	UNE- EN 12004-2: 2017 .
Dangerous substances	See MSDS	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer referred to in point 3

.Rafael Gonzalez Anta,  
General Manager CEMI-COLA PORT SL.

Sagunto, 12 de Febrero de 2020

  
CEMI-COLA PORT, S.L.  
C.I.F. B-97414411  
C/. Isaac Newton/ 83 - Pol. Ind. Sepes  
46500 SAGUNTO (Valencia) España

**CEMI-COLA PORT, SL**

Isaac Newton, 83 – Polígono Industrial Sepes-46500 Sagunto- Valencia- Tel: (34) 96 266 27 62  
www.cemicola.com- cemicola@cemicola.com



0370

CEMI-COLA PORT, SL.  
C/ Isaac Newton, 83  
Pol. Ind. Sepes  
46500 – Sagunto - Valencia España  
04  
C207

UNE- EN 12004-1:2017

**TILE ADHESIVE WHITE QUALITY PORCELANICO**

Cementitious adhesive type C1TE normal setting with reduced slip and extended open time indoors and outdoors.

Reaction to fire	Class E
Initial Adhesion strength	$\geq 0,5\text{N/mm}^2$
Adhesion strength after immersion in water	$\geq 0,5\text{N/mm}^2$
Adhesion strength after heat ageing	$\geq 0,5\text{N/mm}^2$
Adhesion strength after freeze-thaw cycle	$\geq 0,5\text{N/mm}^2$
Slippage	$\leq 0,5 \text{ mm}$
Open time: Adhesion	$\geq 0,5\text{N/mm}^2$ adhesion 30 min
Dangerous substances	See MSDS



**CEMI-COLA**

**CEMI-COLA PORT, SL**

Isaac Newton, 83 – Polígono Industrial Sepes-46500 Sagunto- Valencia- Tel: (34) 96 266 27 62  
www.cemicola.com- cemicola@cemicola.com