



DECLARATION OF PERFORMANCE

In accordance with the European Construction Products Regulation (UE) nº 305/2011

Nº C212

1. Unique identifying code of the product:

TILE ADHESIVE GREY QUALITY FLEX

2. Intended Uses:

Cementitious adhesive for applying ceramic tiles.

Use: indoors and outdoors

3. Manufacturer:

CEMI-COLA PORT, S.L. - C/ Isaac Newton, 83 –
Pol. Industrial Sepes – 46500 SAGUNTO – VALENCIA – ESPAÑA – Tel. 96 2662762
cemicola@cemicola.com – www. cemicola.com

4. System or systems of assessment and verification of constancy of performance of the construction product (EVCP):

Type 3 assessment system

5. Harmonized standard:

UNE-EN 12004-1:2017 Adhesives for ceramic tiles
Notified body: LGAI Technological Center S.A. No 0370

6. Declared performances:

Characteristics	Performance	Test Method
Reaction to fire:	Class E	EN 13501-1
Adhesion:		
Initial Adhesion strength	$\geq 1 \text{ N/mm}^2$	UNE- EN 12004-2:2017
Durability		
- Adhesion strength after immersion in water:	$\geq 1 \text{ N/mm}^2$	
- Adhesion strength after heat ageing:	$\geq 1 \text{ N/mm}^2$	UNE- EN 12004-2:2017
- Adhesion strength after freeze-thaw cycle:	$\geq 1 \text{ N/mm}^2$	
Slippage	$\leq 0,5 \text{ mm}$	UNE- EN 12004-2: 2017
Transverse deformation	$\geq 2,5 \text{ mm}$ y $< 5 \text{ mm}$	UNE- EN 12004-2: 2017
Open time	$\geq 0,5 \text{ N/mm}^2$ Adhesion 30 min.	UNE- EN 12004-2: 2017 .
Dangerous substances	See MSDS	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer referred to in point 3.

.Rafael Gonzalez Anta,
General Manager CEMI-COLA PORT SL.

Sagunto, 12 de Febrero de 2020


CEMI-COLA PORT, S.L.
C.I.F. B-97414411
C/. Isaac Newton/ 83 - Pol. Ind. Sepes
46500 SAGUNTO (Valencia) España

CEMI-COLA PORT, SL

Isaac Newton, 83 – Polígono Industrial Sepes-46500 Sagunto- Valencia- Tel: (34) 96 266 27 62
www.cemicola.com- cemicola@cemicola.com



0370

CEMI-COLA PORT, SL.
C/ Isaac Newton, 83
Pol. Ind. Sepes
46500 – Sagunto - Valencia España
04
C212

UNE- EN 12004-1:2017

TILE ADHESIVE GREY QUALITY FLEX

Cementitious adhesive type C2TES1 improved deformable with reduced slip and extended open time indoors and outdoors.

Reaction to fire	Class E
Initial Adhesion strength	$\geq 1 \text{ N/mm}^2$
Adhesion strength after immersion in water	$\geq 1 \text{ N/mm}^2$
Adhesion strength after heat ageing	$\geq 1 \text{ N/mm}^2$
Adhesion strength after freeze-thaw cycle	$\geq 1 \text{ N/mm}^2$
Slippage	$\leq 0,5 \text{ mm}$
Transverse deformation	$\geq 2,5 \text{ mm y } < 5 \text{ mm}$
Open time: Adhesion	$\geq 0,5 \text{ N/mm}^2$ adhesion 30 min
Dangerous substances	See MSDS



CEMI-COLA

CEMI-COLA PORT, SL

Isaac Newton, 83 – Polígono Industrial Sepes-46500 Sagunto- Valencia- Tel: (34) 96 266 27 62
www.cemicola.com- cemicola@cemicola.com