

# PUTTY FINE PLASTER RENOVATION PASTE



White paste putty fine plaster renovation. **INDOOR**

DESCRIPTION		HOW TO USE	
Indoors	YES	Working time	Indefinite
Outdoors	NO	Drying time	According to layer thickness and environment
Use	Big surfaces	Repainting time	According to environment
Format	1 Kg / 5 Kg / 15 Kg container	Paint compatibility	Good

FEATURES		SUBSTRATES	
Colour	White	Cement - Concrete	YES
Appearance	Very thin white paste	Plaster	If it is very absorbent apply a fixative
PH	7 ± 0,2	Old paint	As long as it is in good condition
Density (average)	1,55 g/cm <sup>3</sup>	Metal	Protect with antioxidant
Adherence	Very good in successive layers	Wood	NO
Performance	350 g/m <sup>2</sup> per meter of layer 1 mm thick	Stone - Brick	YES
Flammable	Non-flammable M.O.		

COMPLEMENTARY INFO		APPLICATIONS	
Pasture	Ready to use material	Gaskets	Yes, very short width
Aplicación	Apply with trowel or spatula	Repair cracks	Yes, very thin
Tool cleaning	Water	Coating gotele	Yes, if it is not very thick (1)
Stored	In dry and insulated interior	Smooth smooth painted surfaces	YES
Expiration	12 months in original container	Fill holes	YES

## DANGER

Danger Non-toxic and fire proof

(1) For very thick goteles use filler putty.

## INDICATIONS OF USE

Plaster gotele, holey and relief paints (indoor). Putty for indoor use, to extend and smooth walls and facades, all kinds of poorly absorbent supports such as walls already painted or lacquered. Also apply on absorbent supports such as plaster and cement. Cover cracks, crevices and holes, very easy to renew putty. Offering excellent results and perfect whiteness.

## WARNING

The information that appears in this data sheet has been obtained from our experience and laboratory tests. These recommendations do not imply any guarantee, since the conditions of application are beyond our control. The customer must ensure that the product is suitable for the use he wishes to use. Do not hesitate to ask our technical service for advice before starting the work.

MANUFACTURED BY **CEMI-COLA, PORT S.L.**

C/ Isaac Newton, 83 / Pol. Ind. Sepes / 46500 Sagunto - Valencia SPAIN / Tel. and Fax (+34) 96 266 27 62 / cemicola@cemicola.com