

PUTTY FINE PLASTER RENOVATION POWDER



White powder putty fine plaster renovation. **OUTDOOR**

DESCRIPTION		HOW TO USE	
Indoors	YES	Working time	5 hours
Outdoors	YES	Drying time	According to layer thickness and environment
Use	Big surfaces	Repainting time	According to environment
Format	5 Kg / 15 Kg bag	Paint compatibility	Good

FEATURES		SUBSTRATES	
Colour	White	Cement - Concrete	YES
Appearance	Smooth fine powder	Plaster	If it is very absorbent apply a fixative
PH	9 ± 0,2	Old paint	As long as it is in good condition
Density (average)	17 g/cm ³	Metal	Protect with antioxidant
Adherence	Very good in successive layers	Wood	NO
Performance	1,58 Kg/m ²	Stone - Brick	YES
Flammable	Non-flammable M.O.		

COMPLEMENTARY INFO		APPLICATIONS	
Pasture	By hand, with catalan palette, spatula or mixer	Gaskets	YES
Aplicación	3 layers: 1 st layer let dry. 2 nd and 3 rd layers: in a row. Wet on wet	Repair cracks	YES
Tool cleaning	Water	Coating gotele	YES
Stored	In dry and insulated interior	Smooth smooth painted surfaces	- Thin layer: Use Putty - Thick layer: (1)
Expiration	12 months in original container	Fill holes	YES

DANGER

Danger Non-toxic and fire proof

(1) If the walls are for leveling in medium or thick layers: 1st scratch the surface, 2nd apply acrylic fixative, 3rd let the support dry, 4th plastering or smooth with the plaster series filled with irregular surfaces, and 5th finish with renewal filler.

WARNING

The information that appears in this data sheet has been obtained from our experience and laboratory tests. These recommendations do not imply any guarantee, since the conditions of application are beyond our control. The customer must ensure that the product is suitable for the use he wishes to use. Do not hesitate to ask our technical service for advice before starting the work.

INDICATIONS OF USE

Putty for indoor and outdoor use, to extend and smooth walls and facades, all kinds of poorly absorbent supports such as walls already painted or lacquered. Also apply on absorbent supports such as plaster and cement. Cover cracks, crevices and holes, very easy to renew putty. Offering excellent results and perfect whiteness.

MANUFACTURED BY **CEMI-COLA, PORT S.L.**

C/ Isaac Newton, 83 / Pol. Ind. Sepes / 46500 Sagunto - Valencia SPAIN / Tel. and Fax (+34) 96 266 27 62 / cemicola@cemicola.com